

Amendments to the Claims

The listing of claims below replaces all prior versions, and listing, of claim in the present application.

Listing of Claims:

1. (Currently Amended) An elevator system comprising:
a hoistway defined by a surrounding structure;
an elevator car and counterweight located in the hoistway; and
a machine, having a drive motor and a drive sheave, located between the elevator car and a sidewall of the hoistway, the drive motor drivingly coupling and suspending the elevator car and counterweight via the drive sheave and at least one flat rope, wherein the flat rope is made from a reinforceable-high traction material and the drive sheave is positioned from the drive motor along the sidewall.
2. (Original) An elevator system as defined in claim 1, further including first and second support columns located on opposite sides of a hoistway relative to each other, each of the support columns extending vertically from a bottom portion to a top portion of the hoistway between the elevator car and said sidewall of the hoistway; and
a support member mounted on and extending generally horizontally between the first and second support columns at a top portion of the hoistway, and wherein the drive motor is supported on the support member.
3. (Currently Amended) An elevator system as defined in claim 2, wherein the counterweight is located underneath the support member between the elevator car and said sidewall of the hoistway, ~~and the drive motor includes a drive sheave drivingly coupling the elevator car and the counterweight via the flat rope.~~
4. (Original) An elevator system as defined in claim 3, further including a counterweight sheave coupled to a top portion of the counterweight, and at least one elevator sheave coupled to

an underside of the elevator car, the flat rope having first and second ends fixedly coupled at a top portion of the hoistway, the flat rope extending downwardly from the first end, looping about the counterweight sheave, extending upwardly and looping about the drive sheave, extending downwardly and underslinging the elevator car via the at least one elevator sheave, and extending upwardly and terminating at the second end.

5. (Original) An elevator system as defined in claim 4, wherein the at least one elevator sheave includes first and second elevator sheaves located at an underside of the elevator car and at opposite sides relative to each other.

6. (Original) An elevator system as defined in claim 4, wherein the first end of the flat rope is coupled to the support member.

7. (Withdrawn) An elevator system as defined in claim 2, wherein ~~the drive motor includes a drive sheave drivingly coupling the elevator car and the counterweight via the flat rope~~, the counterweight is located underneath the support member between the elevator car and the sidewall of the hoistway, the flat rope has a first end coupled to a top portion of the counterweight and a second end coupled to the elevator car, the flat rope extending upwardly from its first end at the counterweight, looping about the drive sheave, and extending downwardly and terminating at its second end at the elevator car to form a 1:1 roping configuration.

8. (Original) An elevator system as defined in claim 2, wherein the first and second support columns respectively include first and second guide members, each of the guide members defining an elevator guide surface extending vertically therealong at least over a length of the support columns corresponding to the path of elevator car travel, and the elevator car defining opposing surfaces shaped to be movably engagable with the elevator guide surfaces as the elevator car moves vertically along the support columns.

9. (Withdrawn) An elevator system as defined in claim 8, wherein each of the first and second guide members further defines a counterweight guide surface extending vertically

therealong at least over a length of the support columns corresponding to the path of counterweight travel, and the counterweight defines additional opposing surfaces shaped to be movably engagable with the counterweight guide surfaces as the counterweight moves vertically along the support columns.

10. (Withdrawn) An elevator system as defined in claim 1, wherein the drive motor is fixedly coupled to one of a ceiling of the hoistway and a sidewall at a top portion of the hoistway.

11. (Withdrawn) An elevator system as defined in claim 10, wherein the drive motor is coupled to a sidewall of the hoistway.

12. (Withdrawn) An elevator system as defined in claim 10, wherein the flat rope has first and second ends each coupled to one of a sidewall and ceiling of the hoistway.

13. (Withdrawn) An elevator system as defined in claim 10, wherein the flat rope has first and second ends each coupled to a ceiling of the hoistway.

14. (Withdrawn) An elevator system as defined in claim 12, wherein the counterweight is located underneath the support member between the elevator car and the sidewall of the hoistway, and including a counterweight sheave coupled to a top portion of the counterweight, at least one elevator sheave coupled to an underside of the elevator car, ~~a drive sheave drivingly coupled to the drive motor~~, and the flat rope extends downwardly from its first end, loops about the counterweight sheave, extends upwardly and loops about the drive sheave, extends downwardly and underslings the elevator car via the at least one elevator sheave, and extends upwardly and terminates at its second end.

15. (Withdrawn) An elevator system as defined in claim 1, further including a first support member extending generally horizontally between and disposed at opposite sides of the hoistway at a top portion of the hoistway between the elevator car and the sidewall of the hoistway, a second support member extending generally horizontally between and disposed at opposite sides

of the hoistway at a top portion of the hoistway between the first support member and the elevator car, first and second deflector sheaves respectively coupled to the first and second support members, a counterweight sheave coupled to a top portion of the counterweight, at least one elevator sheave coupled to an underside of the elevator car, ~~the drive motor including a drive sheave~~, and wherein the drive motor and the drive sheave are disposed at a lower portion of the hoistway between the elevator car and a sidewall of the hoistway.

16. (Withdrawn) An elevator system as defined in claim 15, wherein the flat rope has a first end coupled to the second support member and a second end coupled to one of a ceiling and sidewall of the hoistway at a top portion of the hoistway, the flat rope extending downwardly from its first end, looping about the counterweight sheave, extending upwardly and looping about the first deflector sheave, extending downwardly and looping about the drive sheave, extending upwardly and looping about the second deflector sheave, extending downwardly and underslinging the elevator car via the at least one elevator sheave, and extending upwardly and terminating at its second end.

17. (Withdrawn) An elevator system as defined in claim 15, wherein the flat rope is coupled at its second end to a ceiling of the hoistway.

18. (Withdrawn) An elevator system as defined in claim 15, wherein the at least one elevator sheave includes first and second elevator sheaves located at an underside of the elevator car and at opposite sides relative to each other

19. (Currently Amended) An elevator system comprising:
a hoistway having a wall;
an elevator car traveling within the hoistway
a counterweight traveling within the hoistway;
one or more flat ropes engaged with the elevator car and counterweight to suspend the car and counterweight; and
a drive machine located between the travel path of the elevator car and the wall of the hoistway, the drive machine having a drive motor and a drive sheave and engaged with the one

or more flat ropes through traction to drive the one or more flat ropes and thereby the car and counterweight, wherein the flat rope is made from a reinforceable ~~high~~ traction material and the drive sheave is positioned from the drive motor along the sidewall.

20. (Previously Presented) An elevator system as defined in claim 1, wherein the flat rope is reinforced with steel.

21. (Previously Presented) An elevator system as defined in claim 1, wherein the flat rope is reinforced with fiber.

22. (Currently Amended) An elevator system as defined in claim 1, wherein the ~~high~~ traction material is urethane.

23. (Currently Amended) An elevator system as defined in claim 1, wherein the ~~high~~ traction material is rubber.